



型号	名义倍 数	名义 WD	名义景 深	数值 孔径	分辨率	F/#	畸变	镜身长 度	最小倍 率	最大倍 率	最大 WD	最小 WD	最大接 收器	接口	伸缩长度	图名
I0.02X1000A	0.02	1000	500	0.004	0.084	2.5	0.7	42.5	0	0.45	1000	40	1/3'	C	0~10	IA_T42.5
I0.025X800A	0.025	800	320	0.005	0.067	2.5	0.7	42.5	0	0.45	1000	40	1/3'	C	0~10	IA_T42.5
I0.03X670A	0.03	670	223	0.006	0.056	2.5	0.7	42.5	0	0.45	1000	40	1/3'	C	0~10	IA_T42.5
I0.05X400A	0.05	400	80	0.010	0.034	2.5	0.7	42.5	0	0.45	1000	40	1/3'	C	0~10	IA_T42.5
I0.05X1150A	0.05	1150	230	0.003	0.096	7.2	0.01	42.5	0	0.12	2000	500	1/3'	C	0~10	IA_T42.5
I0.06X960A	0.06	960	160	0.004	0.081	7.2	0.01	42.5	0	0.12	2000	500	1/3'	C	0~10	IA_T42.5
I0.07X850A	0.07	850	121	0.005	0.071	7.4	0.01	42.5	0	0.12	2000	500	1/3'	C	0~10	IA_T42.5
I0.08X750A	0.08	750	94	0.005	0.063	7.5	0.01	42.5	0	0.12	2000	500	1/3'	C	0~10	IA_T42.5
I0.09X670A	0.09	850	94	0.005	0.071	9.6	0.01	42.5	0	0.12	2000	500	1/3'	C	0~10	IA_T42.5
I0.1X145A	0.1	145	15	0.028	0.012	1.8	0.5	42.5	0	0.6	1000	16	1/3'	C	0~10	IA_T42.5
I0.1X170A	0.1	170	17	0.024	0.014	2.1	0.2	42.5	0	0.5	1000	25	1/3'	C	0~10	IA_T42.5
I0.1X190A	0.1	190	19	0.021	0.016	2.4	0.7	42.5	0	0.45	1000	40	1/3'	C	0~10	IA_T42.5
I0.1X250A	0.1	250	25	0.016	0.021	3.1	0.8	42.5	0.1	0.5	250	56	1/2'	C	0~10	IA_T42.5
I0.1X600A	0.1	600	60	0.007	0.050	7.5	0.01	42.5	0	0.12	2000	500	1/3'	C	0~10	IA_T42.5
I0.2X67A	0.2	67	3.35	0.060	0.006	1.7	0.5	42.5	0	0.6	1000	16	1/3'	C	0~10	IA_T42.5
I0.2X70A	0.2	70	3.50	0.057	0.006	1.8	0.2	42.5	0	0.5	1000	25	1/3'	C	0~10	IA_T42.5
I0.2X90A	0.2	90	4.50	0.044	0.008	2.3	0.7	42.5	0	0.45	1000	40	1/3'	C	0~10	IA_T42.5
I0.2X95A	0.2	95	4.75	0.042	0.008	2.4	0.04	42.5	0	0.43	1000	45	1/2'	C	0~10	IA_T42.5
I0.2X120A	0.2	120	6.00	0.033	0.010	3.0	0.8	42.5	0.1	0.5	250	56	1/2'	C	0~10	IA_T42.5
I0.2X160A	0.2	160	8.00	0.025	0.013	4.0	0.4	42.5	0.2	0.5	164	78	1/2'	C	0~10	IA_T42.5
I0.3X40A	0.3	40	1.33	0.100	0.003	1.5	0.5	42.5	0	0.6	1000	16	1/3'	C	0~10	IA_T42.5
I0.3X47A	0.3	47	1.57	0.085	0.004	1.8	0.2	42.5	0	0.5	1000	25	1/3'	C	0~10	IA_T42.5
I0.3X70A	0.3	70	2.33	0.057	0.006	2.6	0.04	42.5	0	0.43	1000	45	1/2'	C	0~10	IA_T42.5
I0.3X85A	0.3	85	2.83	0.047	0.007	3.2	0.8	42.5	0.1	0.5	250	56	1/2'	C	0~10	IA_T42.5
I0.3X100A	0.3	100	3.33	0.040	0.008	3.8	0.2	42.5	0	0.56	1000	60	1/2'	C	0~15	IA_T42.5
I0.3X115A	0.3	115	3.83	0.035	0.010	4.3	0.4	42.5	0.2	0.5	164	78	1/2'	C	0~10	IA_T42.5
I0.3X138A	0.3	138	4.60	0.029	0.012	5.2	0.5	42.5	0.3	0.5	138	98	1/2'	C	0~10	IA_T42.5
I0.3X230A	0.3	230	7.67	0.017	0.019	8.6	0.5	42.5	0.24	0.42	271	183	1/2'	C	0~10	IA_T42.5
I0.4X27A	0.4	27	0.68	0.148	0.002	1.4	0.5	42.5	0	0.6	1000	16	1/3'	C	0~10	IA_T42.5
I0.4X33A	0.4	33	0.83	0.121	0.003	1.7	0.2	42.5	0	0.5	1000	25	1/3'	C	0~10	IA_T42.5
I0.4X50A	0.4	50	1.25	0.080	0.004	2.5	0.04	42.5	0	0.43	1000	45	1/2'	C	0~10	IA_T42.5
I0.4X66A	0.4	66	1.65	0.061	0.006	3.3	0.8	42.5	0.1	0.5	250	56	1/2'	C	0~10	IA_T42.5
I0.4X75A	0.4	75	1.88	0.053	0.006	3.8	0.2	42.5	0	0.56	1000	60	1/2'	C	0~15	IA_T42.5
I0.4X90A	0.4	90	2.25	0.044	0.008	4.5	0.4	42.5	0.2	0.5	164	78	1/2'	C	0~10	IA_T42.5
I0.4X112A	0.4	112	2.80	0.036	0.009	5.6	0.5	42.5	0.3	0.5	138	98	1/2'	C	0~10	IA_T42.5
I0.5X20A	0.5	20	0.40	0.200	0.002	1.3	0.5	42.5	0	0.6	1000	16	1/3'	C	0~10	IA_T42.5
I0.5X25A	0.5	25	0.50	0.160	0.002	1.6	0.2	42.5	0	0.5	1000	25	1/3'	C	0~10	IA_T42.5
I0.5X56A	0.5	56	1.12	0.071	0.005	3.5	0.8	42.5	0.1	0.5	250	56	1/2'	C	0~10	IA_T42.5
I0.5X63A	0.5	63	1.26	0.063	0.005	3.9	0.2	42.5	0	0.56	1000	60	1/2'	C	0~15	IA_T42.5
I0.5X80A	0.5	80	1.60	0.050	0.007	5.0	0.4	42.5	0.2	0.5	164	78	1/2'	C	0~10	IA_T42.5
I0.5X98A	0.5	98	1.96	0.041	0.008	6.1	0.5	42.5	0.3	0.5	138	98	1/2'	C	0~10	IA_T42.5
I0.5X120A	0.5	120	2.40	0.033	0.010	7.5	0.5	42.5	0.45	0.73	125	105	1/2'	C	0~10	IA_T42.5
I1X65A	1	65	0.65	0.062	0.005	8.1	0.5	42.5	0.76	1.05	67	65	1/2'	C	0~10	IA_T42.5

设计		标准		图样标记	重量	比例	www.taopt.com
校对		审定				1:1	
审核		批准					
							IA_T42.5