



型号	倍数	工作距	景深	数值孔径	分辨率	F/#	畸变%	接口	CCD
I0.15X282NM	0.15	282	20.51	0.013	0.026	5.8	0.1	C	1/3'
I0.2X160NM	0.2	161	11.76	0.017	0.020	5.9	0.65	C	1/2'
I0.2X95NM	0.2	95	18.18	0.011	0.031	9.1	0.14	C	1/2'
I0.3X110NM	0.3	110	10.26	0.013	0.026	11.5	0.5	C	1/2'
I0.3X110NM	0.3	113	5.80	0.023	0.015	6.5	0.52	C	1/2'
I0.3X197NM	0.3	197	7.02	0.019	0.018	7.9	0.12	C	1/2'
I0.4X90NM	0.4	90	3.57	0.028	0.012	7.1	0.43	C	1/2'
I0.5X185NM	0.5	180	3.64	0.022	0.015	11.4	0.35	C	1/2'
I0.5X78NM	0.5	78	2.50	0.032	0.010	7.8	0.36	C	1/2'
I0.6X70NM	0.6	70	1.85	0.036	0.009	8.3	0.3	C	1/2'
I0.7X66NM	0.7	66	1.47	0.039	0.009	9.0	0.26	C	1/2'
I0.8X63NM	0.8	63	1.19	0.042	0.008	9.5	0.22	C	1/2'
I0.8X90NM	0.8	90	1.67	0.030	0.011	13.3	0.6	C	1/2'
I0.9X62NM	0.9	62	1.01	0.044	0.008	10.2	0.2	C	1/2'
I1X77NM	1	77	0.93	0.043	0.008	11.6	0.5	C	1/2'

设计		标准		图样标记	重量	比例	www.taopt.com	
校对		审定						1:1
审核		批准						IN_T45.5