



型号	倍数	工作距	景深	数值孔径	分辨率	F/#	畸变%	接口	CCD
I1X90N	1	90	0.80	0.050	0.007	10.0	0.01	C	1/2'
I0.7X128N	0.7	128	1.90	0.030	0.011	11.7	0.01	C	1/2'
I0.7X250N	0.7	251	3.57	0.016	0.021	21.9	0.2	C	1/2'
I0.8X92N16	0.8	92	1.22	0.041	0.008	9.8	0.02	C	1/2'
I1.5X110N	1.5	110	0.73	0.036	0.009	20.6	0.24	C	1/2'
I1X150N	1	150	1.50	0.027	0.013	18.8	0.24	C	1/2'
I2X40N	2	40	0.05	0.085	0.004	11.8	0.2	C	1/2'
I2X45N	2	45	0.80	0.025	0.013	40.0	0.01	C	1/2'
I3.5X50N	3.5	50	0.23	0.050	0.007	35.0	0.04	C	1/2'
I3.5X68N	3.5	68	0.20	0.058	0.006	30	<0.1	C	2/3'
I4X60N	4	60	0.20	0.050	0.007	40.0	0.04	C	1/2'

设计		标准		图样标记	重量	比例	www.taopt.com	
校对		审定						1:1
审核		批准						IN_T81